

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016**Section 1: Identification: Product identifier and chemical identity****Product identifier****Product Name** ANCHORWELD 2701 SUPER CLEAR**Product Code(s)**30608606
30608606; 30608607; 30803689; 30803690**Other means of identification****Proper Shipping Name** Adhesives**UN Number** UN1133**Pure substance/mixture** Mixture**Recommended use of the chemical and restrictions on use****Recommended use** Adhesives**Uses advised against** No information available**Details of manufacturer or importer****Supplier**Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342**ABN:** 79 003 893 838**E-mail address** au-bostik-sds@bostik.com**Emergency telephone number**

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification**GHS Classification**

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

Flammable liquids	Category 2 - (H225)
Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2A - (H319)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

Label elements

Flame
Exclamation mark
Health hazard



Signal word
Danger

Hazard statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P281 - Use personal protective equipment as required
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P235 - Keep cool
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

P308 + P313 - IF exposed or concerned: Get medical advice/attention
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P363 - Wash contaminated clothing before reuse
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

P405 - Store locked up
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Toxic to aquatic life with long lasting effects
In use may form flammable/explosive vapor-air mixture

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Label requirements in accordance with SUSMP

CAUTION

KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No.	Weight-%
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	64742-49-0	30 - 40%
Acetone	67-64-1	20 - 30%
Toluene	108-88-3	20 - 30%
Pentane	109-66-0	0 - 10%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

FIRST AID

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical advice/attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

Section 5: Firefighting measures

Suitable extinguishing media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3YE

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containment Dike far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

containers. Take up mechanically, placing in appropriate containers for disposal.

Precautions to prevent secondary hazards

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Acetone 67-64-1	500 ppm TWA 1185 mg/m ³ TWA 1000 ppm STEL 2375 mg/m ³ STEL
Toluene 108-88-3	50 ppm TWA 191 mg/m ³ TWA 150 ppm STEL 574 mg/m ³ STEL
Pentane 109-66-0	600 ppm TWA 1770 mg/m ³ TWA 750 ppm STEL 2210 mg/m ³ STEL

OEL as published by Safe Work Australia

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Organic gases and vapors filter conforming to EN 14387

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Color clear
Odor Solvent
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	> 55 °C	
Flash point	< 0 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	8.0 (Toluene)	
Lower flammability or explosive limits	1.2 (Toluene)	
Vapor pressure	3-3.5 kPa	
Vapor density	> 1	
Relative density	0.83	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	> 200 °C	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	250 - 400 mPa s	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other information

Solid content (%) No information available
VOC Content (%) 471 g/L
Density No information available

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Irritating to eyes. Causes serious eye irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 43,028.80 mg/kg
ATEmix (dermal) 7,539.10 mg/kg mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	>5000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	=73680 ppm (Rattus) 4 h
Acetone	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Pentane	>2000 mg/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=364 g/m ³ (Rattus) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	Carc. 1A

Reproductive toxicity No information available. Contains a known or suspected reproductive toxin. The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
---------------	----------------------	------	-------------	-----------

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

			Microorganisms	
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)
Pentane 109-66-0	-	LC50: =11.59mg/L (96h, Pimephales promelas) LC50: =9.87mg/L (96h, Oncorhynchus mykiss) LC50: =9.99mg/L (96h, Lepomis macrochirus)	-	EC50: =9.74mg/L (48h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Toluene 108-88-3	2.7
Pentane 109-66-0	3.39

Mobility

Mobility in soil No information available.

Mobility No information available.

Other Adverse Effects

Other adverse effects No information available.

Endocrine Disruptor Information

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

Section 14: Transport information

ADG

UN Number UN1133
Proper shipping name Adhesives
Hazard Class 3
Packing Group II
Special Provisions *
Description UN1133, Adhesives, 3, II

Hazchem code •3YE

IATA

UN number UN1133
Transport hazard class(es) 3
Packing group II
ERG Code 3L
Special Provisions A3
Limited Quantity (LQ) 1 L
Description UN1133, Adhesives, 3, II

IMDG

UN number UN1133
Transport hazard class(es) 3
Packing group II
EmS-No. F-E, S-D
Limited Quantity (LQ) 5 L
Marine Pollutant P
Description UN1133, Adhesives (Naphtha, petroleum, hydrotreated light, <0.1% Benzene), 3, II, (0°C c.c.), Marine Pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Named hazardous chemicals

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III
Liquids with flash points <61°C kept above their boiling points
at ambient conditions

Threshold quantity (T)

50 000
200

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Acetone 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Toluene 108-88-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Pentane 109-66-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AICS	Listed
NZIoC	Not Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

Legend:

- AICS** - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 11-Aug-2019

Revision note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

SAFETY DATA SHEET

ANCHORWELD 2701 SUPER CLEAR
Revision Number 1.01

Revision date 11-Aug-2019
Supersedes Date: 09-Oct-2016

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet